

	Standard	Result
 Size	EN ISO 24342	See separate table
 Thickness	EN ISO 24346	3,0 mm
 Wear layer	EN ISO 24340	0,7 mm
Surface treatment		K-Guard+ PU coating
Guarantee¹	Light industrial Commercial Residential	20 years 20 years 30 years
 Bevelled edge		Standard
 Mass per unit area	EN ISO 23997	5015 g/m ²
 Standards	EN ISO 10582	Heterogeneous PVC
 Classification	EN ISO 10874 - Light industrial EN ISO 10874 - Commercial EN ISO 10874 - Domestic	43: Light industrial heavy 34: Commercial very heavy 23: Domestic heavy
 Reaction to fire	EN 13501-1	B _{fl} -s1
 Staining resistance	EN ISO 26987/EN 423	Excellent
 Light fastness	EN ISO 105-B02	Pass (≥ 6)
 Abrasion resistance	EN 660-2 EN ISO 10582	Group T Type 1
 Flexibility	EN ISO 24344	Pass
 Dimensional stability	EN ISO 23999	Pass (≤ 0,25%)
 Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 2 dB
 Electrical behaviour body voltage	EN 1815	Pass
 Indentation - residual	EN ISO 24343-1	Pass (≤ 0,1 mm)
 Castor chair continuous use	ISO 4918	Pass
 Thermal resistance	ISO 8302	0,0147 m ² K/W Suitable for underfloor heating. Max 27° C
 Slip resistance²	EN 13893 DIN 51130	D5 R10
 Adhesive		Please refer to our recommended adhesive list
 Environmental	French VOC regulation (ISO 16000) Indoor Air Comfort Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration DIBt/AgBB ISO 14001 / ISO 9001	A+ Gold certification; Compliant low emitting VOC emissions. Indoor air quality certified; Compliant low emitting VOC emissions. External third-party verified Type III EPD Pass Manufactured to quality and environment management systems standards
 Recycling		Suitable
 Phthalate free		Yes

¹ Subject to terms see website.

² Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained.

For more information:

Designflooring = T: +44 (0) 1386 820 105 | F: +44 (0) 1386 820 132

Designflooring France = T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH = T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland = T: 020 200 8282 | F: 020 200 8386

Email: info@designflooring.com

www.designflooring.com

05/25



EN 14041: 2004 (DOP 2017/AS/EN/02)
Notified body 0493
Floor coverings (internal)
ISO 10874 Class 23/34/43
Manufactured to ISO 10582



	Product Code	Size		m ²	Box Quantity		Slip Resistance DIN 51130
		mm	inches		Pieces		
Wood Designs	EW03	914,4mm x 1524mm	36,0" x 6,0"	3,345	24 Planks		R10
	RL01	1219,2mm x 177,8mm	48,0" x 7,0"	3,252	15 Planks		R9
	RL13	1219,2mm x 177,8mm	48,0" x 7,0"	3,252	15 Planks		R9
	RL24	1422,4mm x 228,6mm	56,0" x 9,0"	3,252	10 Planks		R9
	RL25	1219,2mm x 177,8mm	48,0" x 4,50"	3,345	24 Planks		R9
	RL26	1422,4mm x 228,6mm	56,0" x 9,0"	3,252	10 Planks		R9
	RL27	1422,4mm x 228,6mm	56,0" x 9,0"	3,252	10 Planks		R9
	RL28	1422,4mm x 228,6mm	56,0" x 9,0"	3,252	10 Planks		R9
	RL31	1422,4mm x 228,6mm	56,0" x 9,0"	3,252	10 Planks		R10
	RL32	1422,4mm x 228,6mm	56,0" x 9,0"	3,252	10 Planks		R10
	RL48	1219,2mm x 177,8mm	48,0" x 4,50"	3,345	24 Planks		R9
	AP01	228,6mm x 76,2mm	9,0" x 3,0"	3,345	192 Planks		R9
	AP02	228,6mm x 76,2mm	9,0" x 3,0"	3,345	192 Planks		R10
	AP03	228,6mm x 76,2mm	9,0" x 3,0"	3,345	192 Planks		R10
	AP05	228,6mm x 76,2mm	9,0" x 3,0"	3,345	192 Planks		R9
	AP08	228,6mm x 76,2mm	9,0" x 3,0"	3,345	192 Planks		R9
	SM-RL20	457,2mm x 76,2mm	18,0" x 3,0"	3,345	96 Planks		R11
	SM-RL22	457,2mm x 76,2mm	18,0" x 3,0"	3,345	96 Planks		R11
	SM-RL23	457,2mm x 76,2mm	18,0" x 3,0"	3,345	96 Planks		R11
	SM-RL24	457,2mm x 76,2mm	18,0" x 3,0"	3,345	96 Planks		R9
	SM-RL26	711,2mm x 114,3mm	28,0" x 4,50"	3,252	40 Planks		R9
	SM-RL27	711,2mm x 114,3mm	28,0" x 4,50"	3,252	40 Planks		R9
	SM-RL28	711,2mm x 114,3mm	28,0" x 4,50"	3,252	40 Planks		R9
	SM-RL31	457,2mm x 76,2mm	18,0" x 3,0"	3,345	96 Planks		R10
	SBW-RL01	114,3mm x 114,3mm / 76,2mm x 304,8mm	4,5" x 4,5" / 3,0" x 12,0"	3,484	192 pieces (96 squares, 96 parquet)		R9
Stone Designs	LM31	457,2mm x 457,2mm	18,0" x 18,0"	3,345	16 Tiles		R10
	LM32	457,2mm x 457,2mm	18,0" x 18,0"	3,345	16 Tiles		R10
	LM33	457,2mm x 914,4mm	18,0" x 36,0"	3,345	8 Tiles		R10
	LM34	457,2mm x 914,4mm	18,0" x 36,0"	3,345	8 Tiles		R10
	LM35	457,2mm x 914,4mm	18,0" x 36,0"	3,345	8 Tiles		R10
	LM36	457,2mm x 914,4mm	18,0" x 36,0"	3,345	8 Tiles		R10
	LM40	457,2mm x 914,4mm	18,0" x 36,0"	3,345	8 Tiles		R10
	LM41	457,2mm x 914,4mm	18,0" x 36,0"	3,345	8 Tiles		R10
	LM42	457,2mm x 914,4mm	18,0" x 36,0"	3,345	8 Tiles		R10
	LM43	457,2mm x 914,4mm	18,0" x 36,0"	3,345	8 Tiles		R10
	LM44	457,2mm x 914,4mm	18,0" x 36,0"	3,345	8 Tiles		R10
	LM45	457,2mm x 914,4mm	18,0" x 36,0"	3,345	8 Tiles		R10