



# Sustainability Data Sheet

Range name	Art Select
Product description	Inherently impermeable and easy to clean due to its PVC construction. A premium decorative floor finish for use in heavy duty residential and commercial areas A heterogeneous (multi-layered), resilient luxury vinyl tile (LVT) floor covering product, designed to be glued with hard-set adhesive.
LVT Format	Gluedown
Type	Wood-look planks
Thickness	3mm
Wear layer	0.7mm Features a moderate surface emboss to aid in aesthetics, slip resistance, and ease of cleaning.
Slip ratings	R9 / P1-P2

## Manufacturing










Independent factory audits	We commission third-party audits of all our factories for both environmental and social performance, which includes working conditions, hours worked, and workplace health and safety.
Manufacturing factory location	Shanghai, China
Primary raw source materials	PVC (41.00%), Filler (44.00%), Plasticizer (13.00%) Ortho-phthalate free
Embodied carbon intensity of the product provided per m <sup>2</sup> (A1-A3)	11.36 Kg CO <sub>2</sub> eq per m <sup>2</sup> with 0 kg CO <sub>2</sub> eq offset
Recycled water used	Our manufacturing partners operate closed-loop water systems, with some facilities using 100% recycled water for industrial processes, significantly reducing reliance on potable water.
Post-industrial recycled content	Up to 50% in the backing layer
ISO14001 certified factory (which provides a framework for measuring and reducing environmental impact, from facility water usage to eco-friendly product packaging)	 <p>Yes - An internationally agreed standard that defines requirements for systems to manage, monitor and control our use of resource and waste.</p>
ISO9001 certified factory (for product-quality management)	 <p>Yes - An internationally recognised standard for quality management systems, helping ensure consistent product quality and continual improvement.</p>

## Supply Chain Transparency



Karndean Global, along with our factory suppliers, are members of Sedex. We use the Sedex framework to assess and improve their sustainability performance. We use independent auditors, Eurofins, and the 4 pillar Sedex framework to review the suppliers on their social performance, environmental performance, business ethics, and labour conditions. Full audit results are made available to customers who are also Sedex members.

## Installation & in use certifications

Stock location	Melbourne, Australia		
Adhesives	Low VOCs, water-based and solvent free adhesives are available		
Packaging:			
Primary Packaging	Cardboard, 100% recyclable		
Tertiary Packaging	Wood pallets, plastic wrapping and banding		
Installation waste	 FOUNDDING MEMBER Clean offcuts can be recycled by ResiLoop		
Crystalline Silica (Quartz) Content (wt%)	Not detected		
PVC Stewardship	 PVC STEWARDSHIP Silver	<b>Environmental Product Declaration (EPD)</b> 	Cradle to Grave/ Full LCA (A1-C4) This product is covered by a third-party, SCS Global, verified Environmental Product Declaration (EPD), specific to this product range. Our EPDs provide transparent, independently verified data that reflects the actual manufacturing, transport, and material inputs relevant to the Australian market.
Floorscore certified	 Yes - awarded low indoor air emissions of Volatile Organic Compounds (VOCs) CERTIFIED BY SCS Global Services	<b>GreenTag™ LCARate</b> 	Silver Plus
Indoor air comfort	 Eurofins Indoor Air Comfort Gold: Awarded to products with low VOC emissions	<b>Best Practice PVC certified</b> 	Yes
		<b>Volatile organic compounds (VOC)</b> 	A+
		<b>Green Building Council Australia (GBCA)</b> 	Yes

## Leadership in Energy and Environment Design (LEED)



Art Select qualifies for the below LEED credits:

Building Type	LEED Credit Description
NC (New Construction)	EQ4.3 Low Emitting Products - Flooring Systems
EB (Existing Buildings)	MR3. Sustainable Purchasing - Facility Alterations
H (Home)	MR2. Environmentally Preferable Products
AWTA to ISO 4760:2022€	Topical Moisture Resistance - Assembled Joint (Modified) with no evidence of water penetration to the substrate through the assembled joint.



## Building Research Establishment Environmental Assessment Method (BREEAM)






Art Select holds the below generic ratings within the BRE Global Green Guide to Specification.

Sector	Element Reference	Rating
Healthcare	821570039	A+
Commercial	821570039	A
Retail	821570039	A+
Education	821570066	A+
Domestic	821570066	A

## End of life and performance data

Warranty		Commercial - 20 years
		Domestic - 35 years
Recyclable		Is warranted to exceed AU building code durability requirements (5 years) when installed in areas appropriate to its ISO 10582 classification assessment.
		Unused installation offcuts are eligible for recycling through the ResiLoop take-back scheme, with a national collection system now in place. This product is designed to minimise on-site waste during installation by maximising material efficiency and reducing offcuts.
Reusable		No
Fire Test Certificate		Available via the Downloads section on our website
Environment Product Declaration (EPD)		<a href="#">Click here</a>

## Brand

The Anti-Greenwashing Charter		Proudly the first Australian company to sign the Anti-Greenwash Charter.	ResiLoop		Founding Member
Modern Slavery Statement		Available upon request	Product Aware profile		Wood-look planks - <a href="#">Oak Royal</a> <a href="#">Handcrafted Parquet</a> <a href="#">Oak Premier</a>
Australian Resilient Flooring Association		Member			