

		STANDARD	RESULT
	Size	ISO 24342	See page 3
	Thickness	ISO 24346	3.0 mm
	Wear layer	ISO 24340	0.7 mm
	Surface treatment		K-Guard+® PU coating
	Warranty ¹	Commercial	20 years wear
		Domestic	Lifetime wear
	Bevelled edge		Standard
	Standards	EN ISO 10582	Pass
	Classification	ISO 10874 - Commercial	34: Commercial very heavy
		ISO 10874 - Domestic	23: Domestic heavy
	Reaction to fire	AS/NZS 9239.1:2003	
	Staining resistance	EN ISO 26987	Excellent
	Light fastness	ISO 105-B02	Pass (≥ 6)
	Abrasion resistance	ISO 10582	Type 1
	Flexibility	ISO 24344	Pass
	Dimensional stability	ISO 23999	Pass (≤ 0.25%)
	Acoustic impact noise reduction ²	EN ISO 717-2/EN ISO 140-8	ΔLw = 2 dB
	Electrical behaviour body voltage	EN 1815	Pass
	Indentation - residual	ISO 24343-1	Pass (≤ 0.1 mm)
	Castor chair continuous use	ISO 4918	Pass
	Thermal resistance	ISO 8302	0.0147 m²K/W
		Underfloor heating	Suitable. Max 27°C
	Slip resistance ³	AS/NZS 4586:2013	See separate table
	Adhesive	General use:	Karndean Mega-Bond
		High temperature:	Two-part chemical cure adhesive or, One-part modified silane heat and moisture resistant adhesive
	Environmental	GBCA/NZGBC GreenStar Rating System	GreenRate Level 'A'; LCA Silver Plus
		FloorScore SCS-EC10.3-2014 v4.0	Certified
		Indoor Air Comfort	Gold
		Environmental Product Declaration	Type III EPD
		NSF/ANSI 332	Conformant product
		ISO 14001 / ISO 9001	Manufactured in certified facilities
	Partnerships	Green Building Council Australia	
		ResiLoop Founding Member	

	Recycling	Suitable
	Phthalate free	Yes

¹ Subject to terms. Please see our website.

² Result is $L_{n,w} = 58$ dB when installed on Regupol 4515 acoustic underlay.

³ Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

Every Karndean range and format meets our certification policy standards – please verify the current certification status

Product Code	Size (mm)	Size (in)	Box qty (m ²)	Box qty (pieces)	Slip Resistance
AP01	228.6 x 76.2	9" x 3"	3.345	192 Planks	R9, P1
AP02	228.6 x 76.2	9" x 3"	3.345	192 Planks	R9, P1
AP03	228.6 x 76.2	9" x 3"	3.345	192 Planks	R9, P1
EW01	914.4 x 152.4	36" x 6"	3.345	24 Planks	R9, P2
EW02	914.4 x 152.4	36" x 6"	3.345	24 Planks	R9, P2
EW03	914.4 x 152.4	36" x 6"	3.345	24 Planks	R9, P2
HC01	914.4 x 152.4	36" x 6"	3.345	24 Planks	R9, P2
HC02	914.4 x 152.4	36" x 6"	3.345	24 Planks	R9, P2
HC03	914.4 x 152.4	36" x 6"	3.345	24 Planks	R9, P2
HC04	914.4 x 152.4	36" x 6"	3.345	24 Planks	R9, P2
HC05	914.4 x 152.4	36" x 6"	3.345	24 Planks	R9, P2
HC06	914.4 x 152.4	36" x 6"	3.345	24 Planks	R9, P2
RL01	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R9, P1
RL02	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R9, P1
RL03	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R9, P1
RL04	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R9, P1