

|                                 | Standard                          | Result                                                      |
|---------------------------------|-----------------------------------|-------------------------------------------------------------|
| Thickness                       | ASTM F386                         | 3.0 mm                                                      |
| Size                            |                                   | See page 2                                                  |
| Wear layer                      | ASTM F410                         | 30 mil <sup>1</sup> (0.7 mm)                                |
| Surface treatment               |                                   | K-Guard+® PU coating                                        |
| Warranty <sup>2</sup>           | Commercial                        | 20 Years                                                    |
|                                 | Residential                       | Lifetime                                                    |
| Beveled edge                    |                                   | Standard                                                    |
| Classification                  | ASTM F1700                        | Class III Type B                                            |
| Reaction to fire                | ASTM E648-06                      | Class 1                                                     |
| Smoke Density                   | ASTM E662-06                      | Pass (< 450)                                                |
| Flammability test               | ASTM D2859                        | Pass                                                        |
| Slip resistance <sup>3</sup>    | ASTM D2047                        | Pass Dry (>0.80)                                            |
| Staining resistance             | ASTM F925                         | Pass                                                        |
| Light fastness                  | ASTM F1515                        | Pass                                                        |
| Abrasion resistance             | ASTM D4060                        | Pass (>50,000 Cycles)                                       |
| Dimensional stability           | ASTM F2199                        | Pass                                                        |
| Acoustic impact noise reduction | ASTM E2179                        | ΔIIC = 9 dB                                                 |
|                                 | ASTM E492                         | IIC = 46 dB (6" Concrete Slab w/Drop Ceiling)               |
|                                 |                                   | IIC = 71 dB (6" Concrete Slab w/Drop Ceiling + QuietChoice) |
| Static load                     | ASTM F970                         | Pass (1,800 psi at 0.005")                                  |
| Indentation - residual          | ASTM F1914                        | Pass                                                        |
| Flexibility                     | ASTM F137                         | Pass                                                        |
| Adhesive                        |                                   | DrySet                                                      |
|                                 |                                   | K-Spray                                                     |
|                                 |                                   | Karndean Epoxy                                              |
|                                 |                                   | K99 HM                                                      |
| Environmental                   | FloorScore® SCS-EC10.3-2014 v4.0  | Certified                                                   |
|                                 | Environmental Product Declaration | Type III EPD                                                |
|                                 | NSF / ANSI 332                    | Conformant product                                          |
|                                 | ISO 14001 / ISO 9001              | Manufactured in certified facilities                        |
| Recycling                       |                                   | Suitable                                                    |
| Phthalate free                  | CPSC-C1001-09.3                   | Yes                                                         |

<sup>1</sup> Nominal

<sup>2</sup> Subject to terms see website.

<sup>3</sup> Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.



# Technical Datasheet

## Art Select - Gluedown

| Plank/Tile | Size (in)     | Size (mm)      | Box qty (ft <sup>2</sup> ) | Box qty (pieces) |
|------------|---------------|----------------|----------------------------|------------------|
| Plank      | 28.0" x 4.5"  | 711.2 x 114.3  | 35.0                       | 40               |
| Plank      | 36.0" x 6.0"  | 914.4 x 152.4  | 36.0                       | 24               |
| Plank      | 48.0" x 7.0"  | 1219.2 x 177.8 | 35.0                       | 15               |
| Plank      | 56.0" x 9.0"  | 1422.4 x 228.6 | 35.0                       | 10               |
| Tile       | 18.0" x 18.0" | 457.2 x 457.2  | 36.0                       | 16               |
| Tile       | 18.0" x 24.0" | 457.2 x 609.6  | 36.0                       | 12               |
| Tile       | 18.0" x 36.0" | 457.2 x 914.4  | 36.0                       | 8                |